

Technical Specifications Of Craneduty

BATLIBOI CRANE & HOIST DUTY 3 PHASE MOTOR FOOT MOUNTED ,TEFC, 415V +/- 10%, 50 Hz +/-6% COMBINE VARIATION +/- 10 % , INSULATION "F" CLASS, PROTECTION IP55, AMBIENT TEMPERATURE 50 DEG C , DUTY S3/S4, CDF 40%, START/STOP 60 PER HOUR REFERING TO IS 325

| kW | HP | RPM | FRAME |
|------|------|------|-------|
| 0.37 | 0.5 | 1000 | 71 |
| 0.55 | 0.75 | 1500 | 71 |
| | | 1000 | 80 |
| | | 750 | 90 S |
| 0.75 | 1 | 1500 | 80 |
| | | 1000 | 80 |
| | | 750 | 90 S |
| 1.1 | 1.5 | 1500 | 80 |
| | | 1000 | 90 S |
| | | 750 | 100 L |
| 1.5 | 2 | 1500 | 90 S |
| | | 1000 | 90 L |
| | | 750 | 100 L |
| 2.2 | 3 | 1500 | 90 L |
| | | 1000 | 100 L |
| | | 750 | 112 M |
| 3.7 | 5 | 1500 | 110 L |
| | | 1000 | 112 M |
| | | 750 | 160 M |
| 5.5 | 7.5 | 1500 | 112 M |
| | | 1000 | 132 S |
| | | 750 | 160 M |
| 7.5 | 10 | 1500 | 132 S |
| | | 1000 | 132 M |
| | | 750 | 160 M |
| 9.3 | 12.5 | 1500 | 132 M |
| | | 1000 | 160 M |
| | | 750 | 160 L |
| 11 | 15 | 1500 | 160 M |
| | | 1000 | 160 L |
| 15 | 20 | 1500 | 160 M |
| | | 1000 | 160 L |
| 18.5 | 25 | 1500 | 160 L |

For any other non-standard requirement please contact us.

Note: Design & development is a continuous activity at Spartan .Design and specifications are subject to change without notice or obligation

Dimensions as per A4-SE-01261 for Foot mounted / A4-SE-01262 for Flange mounted