

Technical Specifications Of Dualspeed

1. 750/1500 RPM - SINGLE WINDING

HP1	HP2	KW1	KW2	FRAME
0.12	0.2	0.09	0.15	71
0.25	0.4	0.18	0.3	80
0.3	0.5	0.22	0.37	80
0.45	0.68	0.33	0.5	90S
0.6	0.8	0.45	0.6	90L
0.8	1.25	0.6	0.93	100L
1	1.6	0.75	1.2	100L
1.5	2.4	1.1	1.8	112M
3	5	2.2	3.7	132S
5	8	3.7	6	132M
6	10	4.5	7.5	160M
8	12.5	6	9.3	160L
10	14	7.5	10.5	180M/L
12.5	16	9.3	12	180M/L
15	20	11	15	200M/L
17.5	25	13	18.5	225S/M
21	30	15.5	22	225S/M

2. 1500/3000 RPM - SINGLE WINDING

HP1	HP2	KW1	KW2	FRAME
0.2	0.25	0.15	0.18	63
0.25	0.33	0.18	0.25	71
0.6	0.8	0.45	0.6	80
0.75	1	0.55	0.75	80
1.2	1.5	0.9	1.1	90S
2	2.5	1.5	1.8	90L
2.5	3	1.8	2.2	100L
3	3.6	2.2	2.7	100L
3.33	4	2.5	3	112M
4	6	3	4.5	132S
5.33	8	4	6	132M
9	12	6.75	9	160M
10	15	7.5	11	160M
15	20	11	15	160L
20	25	15	18.5	180M/L
25	30	18.5	22	180S/M
30	40	22	30	200S/M
50	60	37	45	225S/M

NOTE:

FOR OUTPUT REQUIRED IN BETWEEN ABOVE SELECT NEXT OUTPUT CONNECTION - LOW SPEED DELTA & HIGH SPEED PARALLEL STAR

3. 1000/1500 RPM - SINGLE WINDING

HP1	HP2	KW1	KW2	FRAME
0.5	0.6	0.22	0.37	80
0.6	0.8	0.45	0.6	80
0.8	1	0.6	0.75	90L
1.2	1.5	0.8	1.1	90L
1.6	2.5	1.2	1.8	100L
2	3	1.5	2.2	100L
3	4	2.2	3	112M
4	6	3	4.5	132S
5	7.5	3.7	5.5	132M
7.5	10	4.5	7.5	160M
10	15	7.5	11	160L
12.5	18	9.3	13.5	180M/L
15	20	11	15	180M/L
25	30	18.5	22	200M/L
30	40	22	30	225S/M
35	50	21.5	37	225S/M

NOTE:

FOR OUTPUT REQUIRED IN BETWEEN ABOVE SELECT NEXT OUTPUT CONNECTION - LOW SPEED DELTA & HIGH SPEED PARALLEL STAR